

## Thyristor Surge Suppressor

### Features

- Excellent capability of absorbing transient surge
- Quick response to surge voltage (nS Level)
- Eliminates overvoltage caused by fast rising transients
- Moisture sensitivity level: level 1
- Weight: 70mg
- Non degenerative
- Bi-directional

### Exterior




SMA

### Application Information

- Video

### Package (top view)



### Agency Approvals

Icon	Description
<b>RoHS</b>	Compliance with 2011/65/EU

### Schematic Symbol



### Part Number and Electrical Parameter

Part Number	I <sub>DRM</sub> @ V <sub>DRM</sub>		V <sub>S</sub> <sup>①</sup> @ I <sub>S</sub>		V <sub>T</sub> @ I <sub>T</sub>		I <sub>H</sub>	Co <sup>②</sup>
	μA	V	V	mA	V	A	mA	pF
	MAX		MAX		MAX		MIN	MAX
BS0080M	5	6	25	800	4	2.2	50	60

Absolute maximum ratings measured at T<sub>A</sub> = 25°C RH = 45%-75% (unless otherwise noted).

① V<sub>S</sub> is measured at 100KV/S

② Off-state Capacitance is measured at V<sub>DC</sub>=2V, V<sub>RMS</sub>=1V, f=1MHz


## Thyristor Surge Suppressor

### Part Numbering System

BS 0080 M  
(1) (2) (3)

- (1) Bencent Semiconductor Surge Arrester  
(2) Off-state Voltage, e.g. 0080=6 × 10<sup>0</sup>=6V  
(3) Package: SMA  
(4) Rating Surge Voltage: 3KV (10/700μs)


### Mark



B008M: Part Number  
1312: December, 2013

### V-I Curve

Parameters	Definition
V <sub>DRM</sub>	Peak Off-state Voltage
I <sub>DRM</sub>	Off-state Current
V <sub>S</sub>	Switching Voltage
I <sub>S</sub>	Switching Current
I <sub>H</sub>	Holding Current
V <sub>T</sub>	On-state Voltage
I <sub>T</sub>	On-state Current
C <sub>o</sub>	Off-state Capacitance



### Surge Ratings

Current Waveform	5/320μs*
Voltage Waveform	10/700μs*
I <sub>pp</sub>	75A

-Peak pulse current rating (I<sub>pp</sub>) is repetitive and guaranteed for the life of the product;

-Bencent only makes the test for 5/320μs@75A\* (10/700μs@3KV), but for other IPP value, Bencent will not take any obligation for these parameters, so before applying our parts, please make sure to verify the parameters listed in the above table.



### Thermal Considerations

Symbol	Parameter	Value	Unit
T <sub>J</sub>	Operating Junction Temperature Range	-40 to +150	°C
T <sub>S</sub>	Storage Temperature Range	-60 to +150	°C

### Physical Characteristics

Lead Material	Copper Alloy
Body Material	UL recognized epoxy meeting flammability classification 94V-0
Terminal Finish	100% Matte-Tin Plated

## Typical Characteristics



## Environmental Characteristics


Testing Items	Technical Standards
High Temperature Reverse Bias Test	Temperature: 125±3°C, Bias=80%V <sub>DRM</sub> Time: 168H
High Temperature Life Test	Temperature: 150°C Time: 168H
High-low Temperature Cycle Test	Temperature: From -40°C to 125°C Dwell time: 30min, 10-100 cycles
High Temperature & High Humidity Test	Temperature: 85°C Humidity: 85% Test time: 168H
Pressure Cooker Test	Temperature: 121°C, 2atm. Humidity: 100% Test time: 24H to 168H
Resistance of Soldering Heat	Temperature: 260±5°C Time of dip soldering: 10s, 3times

Note: The above testing items can be specified by customers by contacting Bencent service

## Thyristor Surge Suppressor

Version: A1 2017-12-11


### Product Dimensions



SMA

REF.	mm	inch
A	1.25-1.65	0.049-0.065
B	2.18-2.79	0.086-0.110
C	4.06-4.57	0.160-0.180
D	1.70-2.31	0.067-0.091
E	0.15-0.31	0.006-0.012
F	0.89-1.50	0.035-0.059
G	0.10-0.20	0.004-0.008
H	4.70-5.31	0.185-0.209


### Recommended Soldering Pad



REF	mm	inch
A	6.00	0.236
B	2.00	0.079
C	2.00	0.079


### Reflow Profile

Reflow Condition		Pb-Free Assembly
Pre Heat	Temperature Min.	+150°C
	Temperature Max.	+200°C
	Time (Min to Max)	60 – 180 secs.
Average ramp up rate (Liquidus Temp (T <sub>L</sub> ) to peak)		3°C/sec. Max.
T <sub>S</sub> (max) to T <sub>L</sub> - Ramp-up Rate		3°C/sec. Max.
Reflow	- Temperature (T <sub>L</sub> ) (Liquidus)	+217°C
	- Temperature (T <sub>L</sub> )	60 – 150 secs.
Peak Temp (T <sub>P</sub> )		+(260±0/-5)°C
Time within 5°C of actual Peak Temp (T <sub>P</sub> )		30 secs.
Ramp-down Rate		6°C/sec. Max.
Time 25°C to peak Temp (T <sub>P</sub> )		8 min. Max.
Do not exceed		+260°C



**Package Reel Information**


---



REF	mm	inch
A	2.6+/-0.15	0.102+/-0.006
B	5.15+/-0.15	0.203+/-0.006
d	1.5+/-0.1	0.059+/-0.004
D	330.0	13.0
D1	100+/-3	3.937+/-0.118
D2	13+/-0.3	0.512+/-0.012
E	1.5+/-0.2	0.059+/-0.008
F	5.65+/-0.2	0.222+/-0.008
P	4.0+/-0.2	0.157+/-0.008
P0	4.0+/-0.2	0.157+/-0.008
P1	2.0+/-0.2	0.079+/-0.008
W	12.0+/-0.2	0.472+/-0.008
W1	16.8+/-2.0	0.661+/-0.079

Outline	Reel (pcs)	Per Carton (pcs)	Reel Diameters (mm)	Carton Size(mm)		
				L	W	H
Taping	5,000	80,000	330	360	360	385